




1.1.4 SERIA SAI

V ₁₂₋₂₄₋₄₈₋₁₁₀₋₂₃₀₋₂₄₀ (±10%)			50/60 Hz	Praca ∞
M 16	IP 54			°C -30 +40

Dźwięk ciągły

SAI
SAI
Dźwięk ciągły




Kg. 0,7

V _~	12	24	48
A	1.7	0.9	0.45
dB(A)1m	110	110	110
Hz 600÷20000			

SAI12D	42250	SAI48A	42255
SAI12A	42251	SAI110A	42257
SAI24D	42252	SAI230A	42258
SAI24A	42253	SAI240A	42259
SAI48D	42254		


SAISD12D	42270	SAISD48A	42275
SAISD12A	42271	SAISD110A	42277
SAISD24D	42272	SAISD230A	42278
SAISD24A	42273	SAISD240A	42279
SAISD48D	42274		

SAI SD
SAI SD
Dźwięk ciągły



Dźwięk przerywany

SAI SI
SAI SI
Dźwięk przerywany



Kg. 0,7

V _~	12	24	48	110	230	240
A	1.9	1.1	0.54	0.19	0.12	0.13
dB(A)1m	105	105	105	105	105	106
Hz 800÷15000						

SAISI12D	42360	SAISI48A	42365
SAISI12A	42361	SAISI110A	42366
SAISI24D	42362	SAISI230A	42367
SAISI24A	42363	SAISI240A	42368
SAISI48D	42364		

SAISDSI12D	42369	SAISDSI48A	42374
SAISDSI12A	42370	SAISDSI110A	42375
SAISDSI24D	42371	SAISDSI230A	42376
SAISDSI24A	42372	SAISDSI240A	42377
SAISDSI48D	42373		

SAI SD SI
SAI SD SI
Dźwięk przerywany

