



XLF S PROXIMITY

TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTICS

PRODUCT DESCRIPTION	Low profile LED beacon with three different light options: STEADY LIGHT / FLASHING LIGHT / XENON FLASHING																										
POWER SUPPLY VOLTAGE	12 / 24V AC/VDC 30 ÷ 80V AC/DC (with power supply feeder) 90/240V AC (with power supply feeder)																										
STRUCTURE	<ul style="list-style-type: none"> - PC Body - Opaline dome - PA 6 circuit support - FKM 3075 base gasket / dome - FR4 two-sided internal electronic circuit made up of: <ul style="list-style-type: none"> • Microcontroller for the two light effects • Current regulator to power the LED • 1 POWER LED SMD soldered directly on the circuit <p>5 different types of bases available: (see instruction sheets)</p> <ul style="list-style-type: none"> - SHALLOW - DEEP - FLUSH - WALL - DOUBLE 																										
POWER CONSUMPTION	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th><i>Power consumption mA</i></th> <th>12 VDC</th> <th>24 VDC</th> <th>12 VAC</th> <th>24 VAC</th> </tr> </thead> <tbody> <tr> <td>12/24</td> <td>170</td> <td>100</td> <td>300</td> <td>270</td> </tr> </tbody> </table> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th><i>Power consumption mA</i></th> <th>30 VDC</th> <th>80 VDC</th> <th>30 VAC</th> <th>80 VAC</th> </tr> </thead> <tbody> <tr> <td>30/80</td> <td>150</td> <td>50</td> <td>240</td> <td>100</td> </tr> </tbody> </table> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th><i>Power consumption mA</i></th> <th>110 VAC</th> <th>240 VAC</th> </tr> </thead> <tbody> <tr> <td>90/240</td> <td>80</td> <td>50</td> </tr> </tbody> </table>	<i>Power consumption mA</i>	12 VDC	24 VDC	12 VAC	24 VAC	12/24	170	100	300	270	<i>Power consumption mA</i>	30 VDC	80 VDC	30 VAC	80 VAC	30/80	150	50	240	100	<i>Power consumption mA</i>	110 VAC	240 VAC	90/240	80	50
<i>Power consumption mA</i>	12 VDC	24 VDC	12 VAC	24 VAC																							
12/24	170	100	300	270																							
<i>Power consumption mA</i>	30 VDC	80 VDC	30 VAC	80 VAC																							
30/80	150	50	240	100																							
<i>Power consumption mA</i>	110 VAC	240 VAC																									
90/240	80	50																									
FLASH FREQUENCY	Flash mode : 150 f/min Type of Flash : 5*72 l/min																										
LIGHT OUTPUT	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th>Cd(p)</th> <th>Cd(p)</th> <th>Cd(p)</th> <th>Cd(p)</th> </tr> </thead> <tbody> <tr> <td style="background-color: yellow;">3</td> <td style="background-color: red;">6</td> <td style="background-color: blue;">2</td> <td style="background-color: green;">12</td> </tr> </tbody> </table>	Cd(p)	Cd(p)	Cd(p)	Cd(p)	3	6	2	12																		
Cd(p)	Cd(p)	Cd(p)	Cd(p)																								
3	6	2	12																								
IP RATING	65																										
OPERATING TEMPERATURE	-30° +50°																										
WEIGHT	0.080 kG																										
TECHNICAL DRAWING	SEE INSTRUCTION SHEETS																										



XLF S DIRECTIONAL

TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTICS

PRODUCT DESCRIPTION	Multi-function low profile LED beacon with three light effects: STEADY LIGHT / FLASHING LIGHT / XENON FLASHING EFFECT																										
POWER SUPPLY VOLTAGE	12 / 24V AC/VDC; 30 ÷ 80V AC/DC (with power supply feeder) 90/240V AC (with power supply feeder).																										
STRUCTURE	<ul style="list-style-type: none"> - PC body; - PC fresnel lens dome; - PA 6 support circuit; - Base gasket/dome: FKM 3075; - FR4 Two sided internal electronic circuit made up of: <ul style="list-style-type: none"> o Microcontroller to choose the light effect o Current regulatore to power the LED o 1 POWER LED SMD soldered directly onthe circuit o - 5 different bases available (see instruction sheets): - SHALLOW; - DEEP; - FLUSH; - WALL; - DOUBLE. 																										
POWER CONSUMPTION	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th><i>Power consumption mA</i></th> <th>12 VDC</th> <th>24 VDC</th> <th>12 VAC</th> <th>24 VAC</th> </tr> </thead> <tbody> <tr> <td>12/24</td> <td>170</td> <td>100</td> <td>300</td> <td>270</td> </tr> </tbody> </table> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th><i>Power consumption mA</i></th> <th>30 VDC</th> <th>80 VDC</th> <th>30 VAC</th> <th>80 VAC</th> </tr> </thead> <tbody> <tr> <td>30/80</td> <td>150</td> <td>50</td> <td>240</td> <td>100</td> </tr> </tbody> </table> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th><i>Power consumption mA</i></th> <th>110 VAC</th> <th>240 VAC</th> </tr> </thead> <tbody> <tr> <td>90/240</td> <td>80</td> <td>50</td> </tr> </tbody> </table>	<i>Power consumption mA</i>	12 VDC	24 VDC	12 VAC	24 VAC	12/24	170	100	300	270	<i>Power consumption mA</i>	30 VDC	80 VDC	30 VAC	80 VAC	30/80	150	50	240	100	<i>Power consumption mA</i>	110 VAC	240 VAC	90/240	80	50
<i>Power consumption mA</i>	12 VDC	24 VDC	12 VAC	24 VAC																							
12/24	170	100	300	270																							
<i>Power consumption mA</i>	30 VDC	80 VDC	30 VAC	80 VAC																							
30/80	150	50	240	100																							
<i>Power consumption mA</i>	110 VAC	240 VAC																									
90/240	80	50																									
FLASH FREQUENCY	Flashing mode : 150 l/min Xenon mode : 5*72 l/min																										
LIGHT OUTPUT	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th>Cd(p)</th> <th>Cd(p)</th> <th>Cd(p)</th> <th>Cd(p)</th> </tr> </thead> <tbody> <tr> <td style="background-color: yellow;">800</td> <td style="background-color: red;">1200</td> <td style="background-color: blue;">1000</td> <td style="background-color: green;">2500</td> </tr> </tbody> </table>	Cd(p)	Cd(p)	Cd(p)	Cd(p)	800	1200	1000	2500																		
Cd(p)	Cd(p)	Cd(p)	Cd(p)																								
800	1200	1000	2500																								
IP RATING	65																										
OPERATING TEMPERATURE	-30° +50°																										
WEIGHT	0.080 kG																										
TECHNICAL DRAWING	SEE INSRUCTION SHEETS																										